



## 634-35620 YELLOW OXIDE

PRODUCT 634-35620 IS A CONCENTRATED DISPERSION OF A YELLOW IRON OXIDE PIGMENT IN A SELECT LONG-OIL ALKYD RESIN IN LOW-ODOR MINERAL SPIRITS. THIS COMBINATION IS BROADLY COMPATIBLE AND FINDS USE IN THESE VEHICLES:

- OLEORESINOUS VARNISH
- LONG-OIL ALKYD
- MEDIUM-OIL ALKYD
- SHORT-OIL ALKYD
- STYRENATED ALKYD
- VINYL TOLUENATED ALKYD
- CHAIN STOPPED ALKYD
- SILICONE ALKYD
- PHENOLIC MODIFIED ALKYD
- URETHANE MODIFIED ALKYD
- EPOXY ESTERS
- NITROCELLULOSE

● = PRIMARY USE      ○ = SECONDARY USE

THIS PIGMENT IS THE LARGE-CRYSTAL OPAQUE FORM OF PIGMENT YELLOW 42. THIS IS A HIGH-PURITY PRECIPITATED GRADE WHICH HAS BEEN DRY MICRONIZED PRIOR TO THE FINAL WET GRINDING PROCESS. PAINTS MADE USING THIS DISPERSION EXHIBIT HIGH GLOSS AND HIGH HIDE EVEN AT LOW FILM THICKNESS.

### LIGHT RESISTANCE:

FULL SHADE	EXCELLENT
TINT	EXCELLENT

### SOLVENT RESISTANCE:

MINERAL SPIRITS	EXCELLENT
TOLUENE	EXCELLENT
LACQUER	EXCELLENT

### PRODUCT CONSTANTS:

WEIGHT/GALLON	13.7 LBS.
PERCENT NVM	76.6%
PIGMENT YELLOW 42	60.0%
V.O.C./GALLON	3.2 LBS.

### CHEMICAL RESISTANCE:

ACID	EXCELLENT
ALKALI	EXCELLENT

**HEAT RESISTANCE:** 320°F.

Date: 19 December 02